



Name of product:

Cable CobiCabling CAT. 6 U/UTP PE45 0MHz outdoor dry Fca 500m

Part number:


C13-6900

FEATURES:

- 450MHz frequency (CAT. 6)
- Length marker every 1m
- Outdoor cable with PE sheath

PRODUCT DESCRIPTION:

CobiCabling category 6 unshielded cable PE is designed to exceed requirements of EN 50173-1:2018-07, EN 50173-1:2018, ISO/IEC 11801:2017 with additional margin in all parameters. Our CAT. 6 cable is used in high-speed networks, including Gigabit Ethernet. In combination with our patch panels and RJ45 modules, it provides a reliable foundation for any network.



COMPLIANCE WITH THE REQUIREMENTS OF STANDARDS:

- EN 50173-1:2018-07
- ISO/IEC 11801:2017
- ANSI/TIA-568-D.0/D.1/D.2
- IEC 60754-2/A1:2020
- IEC60332-1-2/A12:2021

TYPICAL APPLICATIONS:

- 100Base-TX Fast Ethernet;
- 1000Base-T Gigabit Ethernet;
- Composite Video;
- ATM-25/52/155 Mbit/s, Token Ring
- PoE, PoE+, 4PPoE

Feature	Values
Frequency	Tested to 450MHz
Outer sheath	PE black colour
Compatible with	6
Shielding	U/UTP
Length marking	from 500 to 0 (marked every 1m)
NVP	69% (0,69)
Outer diameter	6,0mm (±0,2mm)
Conductor diameter	23AWG
Euroclass	Fca
Temperature range	During installation -10°C do +50°C, During operation -30°C do +80°C