

DATASHEET

Wall distributor splice housing W=430 x H=330 x D=100mm, without panels



General data

Housing with two swing doors, lockable,
 2 different locks with 2 keys each
 With 2 cable entry openings at the top and bottom
 for PG16 plus 2 cable entry openings
 with sealing strip
 Additional strain relief clamps and guides
 for fiber and cable storage for fastening
 with cable ties. Max. 5 splice cassettes and one
 Distributor plate can be mounted.
 Up to 6 Pro splice cassettes can be mounted
 The distribution plate is fastened in two ways
 M3 screws.
 Dimensions (W) x (H) x (D) 430 x 330 x 100 mm
 Sheet steel 1.2 mm, weight approx. 4.6 kg

Allgemeine Daten

With housing	True
Suitable for number of module inserts	5
With front plate	False

This datasheet was created automatically on 16-08-2024 . Technical changes reserved.



DATASHEET

Wall distributor splice housing W=430 x H=330 x D=100mm, without panels

Mounting method	Wall mounting
With pigtails	False

General data

Height	330 mm
--------	--------

Abmessungen

Width	430 mm
-------	--------

Dimensions

Depth	100 mm
-------	--------

Available variants

ArtNr.	Bezeichnung	Colour	RAL-Nummer
53604.1V2	Wall distributor splice housing W=430 x H=330 x D=100mm, without panels	grey	7035

This datasheet was created automatically on 16-08-2024 . Technical changes reserved.

